

2.4Ghz 300Mbps WiFi Range Extender

802.11n, 1-Port, Wall-plug, QR-Code for mobile devices

Model: GDI310C



Introduction:

The GDI310C is a special version wifi range extender designed for mobile devices , with QR-Code for mobile phone and tablet to scan and login, It makes setup much easier. Also it has signal strength indicator for best installation place remind, which help boost your existing WiFi network to places out of reach of your existing WiFi.

QR-Code scan to log in

No need to configure your PC settings, mobile phone connects to repeater's network, scan the QR code, help the non-tech savvy enjoy the easiest user experience .

Easy to setup with any type router

Press the WPS button on your router and the Range Extender button on GDI310C within 2 minutes to finish setup, get quick and secure connection. For non WPS button older type router, GDI310C's easy-to-install wizard gives you same 2 minutes speed to finish setup effortlessly.

More AP and Client mode as you need

GDI310C also can turn Ethernet port in your hotel room into your own personal Wi-Fi hotspot, create a New Wi-Fi Network. Moreover, this device additionally supports Client Mode, so you can integrate LAN based devices into your wifi network.

Signal indicator to find the best location

GDI310C additionally has intelligent LED indicator, it assists you with the best location indicator with a simple, color-coded light.

- Simple , color-coded light smartly indicate the perfect location
- Compact size but powerful in extending Wi-Fi range

Specification:

Chipset	MTK7628KN
Standard	802.11/b/g/n, MIMO technology
Memory	64Mbit(8MByte) DDR1 RAM
Flash	16Mbit(2MByte)
Interface	1 * 10/100 RJ45 LAN Port
	1 * WPS/ Reset button
LED Light	Power / Ethernet/ Wireless on/off
Antenna	Internal Omni Antenna
Power Supply Unit	100v-240v AC
Power consumption	3W
Size	L:70 x W:56 x D:30 mm
Weight	120g
Frequency	2.4-2.4835GHz
Wireless Transmit Power	14 ~18dBm (Typical)
Wireless Signal Rates	11n: Up to 300Mbps(dynamic)
	11g: Up to 54Mbps(dynamic)
	11b: Up to 11Mbps(dynamic)
Modulation	OFDM = BPSK,QPSK, 16-QAM, 64-QAM
	DSSS = DBPSK, DQPSK, CCK
Throughput	300 Mbps
Operation mode	WiFi Repeater, Wireless AP, Client
Wireless Security	64/128-bit WEP, WPA / WPA2, WPA-PSK/ WPA2-PSK encryption
WPS	PIN.PBC
Package Contents	300Mbps WiFi range extender Ethernet Cable Quick Installation Guide
System Requirements	Microsoft Windows 98SE, NT, 2000, XP, Vista™ or Windows 7, Windows 8, Windows 10, MAC OS, NetWare, UNIX or Linux
Environment	Operating Temperature: 0~40 °C (32 °F~104°F) Storage Temperature: -40~70 °C (-40 °F~158°F) Operating Humidity: 30%~90% non-condensing; Storage Humidity: 30%~95%non-condensing



12400 SW 134 CT Ste 14
Miami FL 33186

Ph 305.969.2047
Fax 305.969.8853

sales@gditechnology.com
www.gditechnology.com