

WE CUSTOMIZE FEATURES

To meet your needs





Overview

GDRC-DTA2 Remote control is the newly designed 2 in1 remote control that allows you to control 2 devices of TV & CBL. You can program your Remote Control to operate most models and brands of infrared remote-controlled TV's in the world, including the most updated codes for Flat Screen TV.

Features at a Glance

- Controls up to 2 Device (TV, Cable STB)
- IR code database for most popular TV Brands
- · Reduced number of keys for simple interface
- Designed to operate Digital-to-Analog converters
- Easy Set up
- · Custom Logo available
- Low Energy IR for 3-Year Battery Life*

Applications

TV, Cable STB



SPECIFICATIONS

MODEL NUMBER:

• GDRC-DTA2

MATERIALS:

- · Plastic housing ABS
- Keypad silicon rubber

PACKAGING:

- Each unit individually wrapped in polyethylene bag
- · Each unit ships with one manual
- Units per case: 250

WARRANTY:

· Mechanical: 12 months

POWER SUPPLY:

2 AAA batteries (not included)*

TRANSMIT RANGE:

- Direct line of sight: 50 feet (15 m)
- 30 degree angle: 20 feet (7m)

DIMENSIONS:

Lenght: 5.6 in (144 mm)Width: 1.7 in (44 mm)Depth: 1.2 in (31 mm)

NUMBER OF KEYS:

• 23

IR SUPPORT:

• 1 IR LEDs

Simple Code Search

Program **GDRC-DTA2** for any brand in 3 easy steps by following the setup instructions printed in the manual.

GDRC-DTA2 REMOTE CONTROL





3-Year Battery Life based on 2 new heavy duty batteries in a non-backlit remote under normal use conditions

GDI Technology reserves the right to make changes to the product at any time without notice. Information provided by GDI Technology is believed to be accurate and reliable. However, no responsibility is assumed by GDI Technology for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

GDI Technology products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.